

## LU tape



### Product description

LU tape is used for sealing ducts.

|                  |   |
|------------------|---|
| Construction     | polyethylene coated textile fabric  |
| Type of adhesive | rubber glue   |
| Installation     | surfaces must be clean and free of moisture and contamination                                     |
| Storage          | max 12 months, if stored at +21°C and relative humidity up to 50%, protected from direct sunlight |
| Colour           | Silver  |

| Technical specifications |                |
|--------------------------|----------------|
| Properties               | Value          |
| Total thickness          | 150 micron     |
| Adhesion                 | 15 N/25mm      |
| Tack rolling ball        | 20 cm          |
| Strength                 | 60 N/25mm      |
| Elongation               | 12.0 %         |
| Intermittent temperature | -20°C to +60°C |
| Constant temperature     | +10°C to +40°C |

| Dimensions   |           |           |       |
|--------------|-----------|-----------|-------|
| Product code | Width, mm | Length, m | m, kg |
| LU38-10      | 38        | 10        | 0,1   |
| LU38-25      | 38        | 25        | 0,2   |
| LU38-50      | 38        | 50        | 0,3   |
| LU48-10      | 48        | 10        | 0,1   |
| LU48-25      | 48        | 25        | 0,2   |
| LU48-50      | 48        | 50        | 0,4   |